# ButterflyMX Security Cameras

Enhance security and convenience at your property

Gain complete visibility throughout your property while easily integrating with the ButterflyMX ecosystem of access control products. Designed specifically for multifamily, gated communities, student housing, and commercial properties, ButterflyMX Security Cameras provide you with a unified system that connects property access to live video for enhanced security and convenience.

EASY INSTALLATION:
Our Security Cameras can be installed in minutes with a single PoE connection, eliminating additional wiring.

SEAMLESS INTEGRATION:
Connect ButterflyMX cameras to our suite of access control products to see live video in the ButterflyMX OS.

STANDALONE OR FULL-SUITE INTEGRATION:
Use as a standalone solution or integrate with ButterflyMX's access control system for a single, unified system.

VERSATILE & DURABLE:
Choose from two camera models suitable for entryways, garages, lobbies, amenity spaces, parking lots, or any other indoor or outdoor space.

90-DAY CLOUD STORAGE:
Store video securely in the cloud for up to 90 days.

CAMERA COMPATIBILITY:
Keep your current ONVIF IP security cameras by installing our Camera Gateway.

24/7 HD VIDEO RECORDING:
Capture every moment in 1080p high-definition at 15 frames per second.

VIDEO FILTERING:
Filter video by entry events to quickly see the footage that matters most.

LIVE CAMERA MULTI-VIEW:
View up to 40 live camera feeds in a single grid from the ButterflyMX OS.

HARDWARE SPECIFICATIONS

ButterflyMX Bullet

Dimensions: 2.7" W x 7.9" L x 2.5" H

- Long-range coverage Ultra HD streaming up to 50 feet.
- Wide-angle view with 104.7° field of view and 180° pan/tilt.
- 18 infrared LEDs provide crisp night vision in low-light conditions.
- IP66-rated with 4000V of lightning protection for outdoor use.
- Continuous 1080p HD streaming with H.264 compression at 15fps.
- Operates from -22°F to +140°F with low 8W PoE+ power draw.

ButterflyMX Dome

Dimensions: 4.3" W x 4.3" L x 3.7" H

- Discreet design with Ultra HD streaming and 50 feet of clear visibility.
- Varifocal lens adjusts from 2.8-12mm for right or wide shots.
- Infrared night vision up to 95 feet with 18 built-in IR LEDs.
- IP66 weather resistance, IK10 impact resistance, and 4000V lightning protection.
- 90° vertical tilt for added coverage of large spaces.
- Streams and records 1080p HD video at 2000 kbps.
- Performs in extreme temperatures with PoE power connection.

ButterflyMX Camera Gateway

Dimensions: 2.6" W x 3.5" L x 1.6" H

- Connect up to 10 Security Cameras with ButterflyMX's suite of property-wide access control products.
- Compact design, weighing only 0.5 lb to easily fit into any secure, weatherproof location.
- Connect up to 10 ONVIF-compatible cameras for seamless integration with the ButterflyMX OS.
- Powered by a Broadcom 2.4GHz quad-core 64-bit Arm Cortex a-76 for fast, reliable performance.
- Includes 1TB of local SSD storage for secure, on-site video retention.
- Connects via Ethernet (10/100/1000 Mbps) for stable, high-speed network performance.
- Runs on 5V/5A DC power via USB-C with low power consumption of just 7 watts.
- Operational in temperatures 50°F and 85°F.
- Requires a minimum of 600 Kbps of internet bandwidth per stream.