

# 7" SURFACE MOUNT INTERCOM

(see pages 2 and 3 for measurements)



# **TOUCHSCREEN**

Brightness: 1000 NitsDiagonal length: 7"

• Resolution: 1024 x 600

• Contrast ratio: 700:1

Capacitive touch

• IP65 dust and water resistance

• Chemical resistant/ Anti-glare coated



### **COMPLETE SYSTEM**

- Bluetooth connectivity
- Touch screen withstands a 225g drop ball test from 1.6 meters
- Designed for standard power socket: NEMA 5-15
- Max temperature: +60° C/+140° F



### **DIMENSIONS**

- 12.44" x 7.539" x 2.027"
- 316.0mm x 191.5mm x 51.5mm



## POWER REQUIREMENTS

- Intercom input voltage: 24VDC
- Standard power consumption:
   31W at 24VDC input
- Maximum power consumption:
   65W at 24VDC input
- Relay max switching current: 5A, relay max switching power: 1250W
- No AC power directly connected to intercom
- Coordinate dedicated electrical circuit on UPS (power conditioned)



#### **NETWORK REQUIREMENTS**

- 2 Mbps ethernet connection Cat5e/Cat6
- No WiFi
- No DSL
- IP assigned by DHCP by default for static IP assignment call support
- 4G SIM card is supported (refer to building network requirements for details)



### **MISC.HARDWARE SPECIFICATIONS**

- For camera angle adjustment, call support
- For the installation of the backplate, M4 countersink screws will be needed (not provided)

# **Support:**

P: **(800)** 398-4416 ext. 2 (Mon-Fri, 6am-10pm EST)

E support@butterflymx.com

SUPPORT:


P: (800) 398-4416 ext. 2 (Mon-Fri, 6am-10pm EST) E: support@butterflymx.com **DRAFT SUBJECT TO CHANGE** 


**VERSION:** 7-S-Cutsheet-Comp-v12-2022-11-30 **PAGE:** 2 of 3


PORT/

SIM SLOT


**SCALE:** Not to scale








# 1 INTERCOM FRONT ELEVATION NOT TO SCALE



2 INTERCOM REAR ELEVATION




OUTPUT #4 #3

POWER

BUTTON

NOT TO SCALE



**BACKPLATE FRONT ELEVATION** 

INTERCOM TOP/BOTTOM VIEW



6 INTERCOM REAR w/ BACKPLATE

The following plans are diagramatic. It will be up to the installation contractor to coordinate with associated trades to formalize a complete submission for installation. Intercom mounting height to be ADA Compliant.



TITLE: 7" Surface Mount Intercom


**DRAWING SCALE:** Not to scale

#### SUPPORT:

P: (800) 398-4416 ext. 2 (Mon-Fri, 6am-10pm EST) E: support@butterflymx.com **DRAFT SUBJECT TO CHANGE** 


**VERSION:** 7-S-Cutsheet-Comp-v12-2022-11-30





**ADA Compliance Requirement** 





2 FRONT VIEW: BACKPLATE PLACEMENT NOT TO SCALE